

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/012034 A1

(51) International Patent Classification⁷: **B60N 2/48**

(74) Agents: SIMONELLI, David, J. et al.; Clark Hill PLC,
Suite 3500, 500 Woodward Avenue, Detroit, MI 48226-
3435 (US).

(21) International Application Number:
PCT/US2004/025720

(22) International Filing Date: 28 July 2004 (28.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/490,499 28 July 2003 (28.07.2003) US

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AI, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(71) Applicant (for all designated States except US): **INTIER
AUTOMOTIVE INC.** [CA/CA]; 521 Newpark Blvd.,
Newmarket, Ontario L3Y 4X7 (CA).


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SI, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

(72) Inventor: and

(75) Inventor/Applicant (for US only): **NEALE, Colin, Ge-
offrey** [US/US]; 39473 Village Run Drive, Northville, MI
48167 (US).

[Continued on next page]

(54) Title: **TILTING HEAD RESTRAINT WITH A USE POSITION AND A STOWED POSITION**



(57) Abstract: A head and restraint assembly for a motor vehicle seat having a seat back includes a support member (20) that is removably securable to the seat back. A body portion (12) including a foam cushion is disposed adjacent the support member. A pivot tube (28) is fixedly secured to the support member. The pivot tube defines a slot cut (40, 42) through the pivot tube. A spring (38) is fixedly secured to the pivot tube and extends through a portion of the pivot tube. The head restraint assembly also includes a pivot rod (54) that is disposed within the pivot tube. The pivot rod includes a guide pin (56, 58) that extends out of the pivot rod and is received by the slot. The pivot rod is fixedly secured to the body portion such that rotation of the pivot rod with respect to the pivot tube pivots the body portion with respect to the support member to move the body portion between a use position and a stowed position.



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.